



# Microsoft

## Exam Questions 98-375

HTML5 Application Development Fundamentals

Version: Demo

1. You add script tags to an HTML page. You need to update the text value within a specific HTML element. You access the HTML element by id. What should you do next?

- A. Use the `createTextNode` method.
- B. Use the `appendChild` method.
- C. Set the new text value with the `setAttribute` method.
- D. Use the `firstChild` property and set the new text value with the `nodeValue` property.

**Answer: D**

2. Which attribute prefills a default value for an input element in HTML5?

- A. `name`
- B. `placeholder`
- C. `autocomplete`
- D. `required`

**Answer: B**

3. Which code fragment will display the Play and Pause controls in the audio interface?

A. `<audio controls="controls">`

B. `<audio preload="controls">`

C. `<audio preload="auto">`

D. `<audio autoplay="autoplay">`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer: A**

#### 4. DRAG DROP

Match the HTML5 input attributes to the corresponding descriptions. (To answer, drag the appropriate attribute from the column on the left to its description on the right. Each attribute may be used once, more than once, or not at all. Each correct match is worth one point.)

| Attribute   | Description  |
|-------------|--|
| maxlength   | provides a way to set a regular expression that the value must match       |
| multiple    | provides a way to set default text until focus is placed in an element     |
| pattern     | provides a way to set form elements as mandatory                           |
| placeholder | provides a way to allow more than one file email address in a single input |
| required    |  |

Answer:

| Attribute   | Description   |
|-------------|---|
| maxlength   | pattern provides a way to set a regular expression that the value must match        |
| multiple    | placeholder provides a way to set default text until focus is placed in an element  |
| pattern     | required provides a way to set form elements as mandatory                           |
| placeholder | multiple provides a way to allow more than one file email address in a single input |
| required    |   |

5. You create an interface for a touch-enabled application.

You discover that some of the input buttons do not trigger when you tap the screen.

You need to identify the cause of the problem.

What are two possible causes? (Choose two.)

- A. The input areas overlap with other input areas.
- B. The touch screen is not initialized.
- C. The input areas are using event handlers to detect input.
- D. The defined input areas are not large enough.

**Answer:** A,D

6. Which three generic font family names are valid values of the font-family property in CSS? (Choose three.)

- A. cursive
- B. system
- C. serif
- D. fixed
- E. fantasy

**Answer:** A,C,E

Explanation: There are five generic fonts: serif, sans-serif, monospace, cursive and fantasy.

Note:

There are two types of font family names:

family-name - The name of a font-family, like "times", "courier", "arial", etc.

generic-family - The name of a generic-family, like "serif", "sans-serif", "cursive", "fantasy", "monospace".

7. The variable named "ctx" is the context of an HTML5 canvas object. What does the following code fragment draw? `ctx.arc(x, y, r, 0, Math.PI, true);`

- A. a circle at the given point
- B. a square at the given point
- C. a semi-circle at the given point

D. a line from one point to another

**Answer: C**

8. You create an instance named "location" of a geolocation object.

Which code fragment will initiate periodic updates of a device's geographic location?

- A. `location = navigator.geolocation;`
- B. `location.watchPosition(showLocation) ;`
- C. `location.getCurrentPosition(showLocation);`
- D. `location.clearNatch(watchid);`

**Answer: B**

9. DRAG DROP

Match the CSS position property values to the corresponding descriptions. (To answer, drag each value from the column on the left to its description on the right. Each value may be used once, more than once, or not at all. Each correct match is worth one point.)

| Position Property Value | Description  |
|-------------------------|--|
| fixed                   | Element appears in the order in which it is placed in the document flow. |
| static                  | Element is positioned relative to the first positioned ancestor.         |
| inherit                 | Element is positioned relative to the browser window.                    |
| relative                | Element is positioned based on its parent element's position.            |
| absolute                |  |

**Answer:**

| Position Property Value | Description   |
|-------------------------|---|
| fixed                   | <div style="border: 1px solid red; padding: 2px;">static</div> Element appears in the order in which it is placed in the document flow. |
| static                  | <div style="border: 1px solid red; padding: 2px;">absolute</div> Element is positioned relative to the first positioned ancestor.       |
| inherit                 |   |
| relative                | <div style="border: 1px solid red; padding: 2px;">fixed</div> Element is positioned relative to the browser window.                     |
| absolute                | <div style="border: 1px solid red; padding: 2px;">inherit</div> Element is positioned based on its parent element's position.           |

10. Which tag is used to create a drop-down list in HTML5?

- A. <ul>
- B. <select>
- C. <datalist>
- D. <dd>

**Answer: B**

## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### 98-375 Practice Exam Features:

- \* 98-375 Questions and Answers Updated Frequently
- \* 98-375 Practice Questions Verified by Expert Senior Certified Staff
- \* 98-375 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* 98-375 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The 98-375 Practice Test Here](#)**